

CatTail.03 – Product Specification



Cat Tail.03

Just because the Cat Tail.03 is the shortest in its class, doesn't mean it's short on fun. Don't be mistaken. Sometimes big surprises come in small packages!



Cat Tail.03 – at a glance.

Product Family:	Playpoints	Number of Foundations:	1 pc.
Item Number:	90.260.203	Concrete Volume C20/C25:	0.5 m³ (18 ft³)
Children's Age:	5+	Number of skilled installers required:	2
Fall Height (DIN EN 1176):	0.4 m (1'-4")	Installation Time without foundation:	2 hours
Length x Width x Height:	0.7 m x 0.4 m x 1.9 m (2'-4" x 1'-4" x 6'-3")	Dimensions of largest part:	0.7 m x 0.4 m x 2.4 m (2'-4" x 1'-4" x 7'-11")
Protective Surfacing Area (DIN EN 1176):	3.6 m x 3.6 m	Weight of the heaviest part:	45 kg (100 lbs)
Protective Surfacing Area (ASTM 1487):	4.3 m x 4.3 m (14'-2" x 14'-2")	Shipping Volume:	1.4 m³ (50 ft³)
Minimum space required DIN EN 1176:	10.2 m²	Shipping Weight:	75 kg (166 lbs)
Minimum space required ASTM 1487:	14.3 m² (154 ft²)	Spare part guarantee:	Lifelong
		Certificate according to DIN EN 1176:	No.: Z2 15 07 10256 237 TÜV Product Service

Technical Data.

The following text can also be used for tenders.

Base plate:

Stainless steel plate Ø 320 mm (1'-1"), covered with HDPE panels, 19 mm (3/4") thickness

Tubes:

Stainless steel tubes, Ø 48,3 & 40,0 mm (1'-7" & 1'-4"), slightly bended, connected to an Frameworkor®-aluminum ball connector; Ø 200 mm (8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-cap

Luffing mechanism:

Fully encapsulated rubber-metal-bearing integrated in stainless steel foundation tube

Covering:

Antiskid HDPE panels, 19 mm (3/4"), bolted on the base plate


Berliner
Berliner Seilfabrik GmbH & Co.
Lengeder Straße 2/4
D-13407 Berlin

Tel. +49.(0)30.41 47 24-0
Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com
www.berliner-seilfabrik.com

